### STATE OF MAINE

### COMMERCIAL VEHICLE LAWS & REGULATIONS

Effective December 16, 2009

Reference to Maine Revised Statutes Annotated, Title 29-A

Prepared By The Bureau of Motor Vehicles,

Office of Motor Carrier Services

With the Advice and Consent of

Maine Department of Transportation and

Maine Department of Public Safety

# CONTACTS FOR COMMERCIAL VEHICLE INFORMATION, LAWS, and REGULATIONS

Traveler Information, Weather, Posted & Restricted Roads: Internet Web Site Address: www.511maine.gov Telephone: 511

Bureau of Motor Vehicles (BMV):

Internet Web Site Address: www.maine.gov/sos/bmv/commercial

Telephone: (207) 624-9000 + Extension

Telephone: (207) 624-9000 + Extension	
	Extension
Administrative Services	
Main Switchboard	52155
Driver License Services	
Accidents	52110
Administrative Hearings	52113
Court Records	
Driving Records	
Financial Responsibility	
License Examinations (Auto)	
License Examinations (Commercial)	
Medical Review	
OUI	
Renewals/Changes/State IDs	
Vehicle Services	
Container Permits	52134
Dealer Licensing	
For Hire Insurance	
Fuel Tax Reporting (IFTA)	
Fuel Tax Decals	
Heavy Vehicle Use Tax	
Operating Authority/Unified Carrier Registration	
Overlimit Permits	
Registrations	52134
Auto	E2240
IRP Commercial	
Non IRP Commercial	
Trailer	
ALGALUL	52151

Special Mobile Equipment	52151
Titles	
USDOT Numbers	
E-mail:	
Vehicle Services	
Container Permitsoverpermits@n	naine.gov
For Hire Insuranceforhireins@n	
Fuel Tax Reporting (IFTA)IFTA.BMV@n	maine.gov
Fuel Tax DecalsIFTA.BMV@n	maine.gov
Motor Carrier Services AdminMCSAdmin.BMV@n	
Heavy Vehicle Use TaxHVUT.BMV@n	-
Operating Authority/UCRucr@n	and the second second second second
Overlimit Permitsoverpermits@n	
Registrations	
IRP Commercialmeirp@n	naine gov
TrailerTrailerUnit.BMV@m	The second liverage with the second liverage w
TitlesTitles.BMV@n	
USDOT Numbers	
	and igo
Other Contacts:	
Drug Test Requirements (FMCSA)(207)	622-8358
Explosives Transport	022 0000
State Regulations/Permits(207)	626-3880
Federal Regulations/Permits(207)	
Fuel Tax Audits (Maine Revenue Services)(207)	
Hazardous Materials Transport	024 2000
State Regulations(207)	624-8939
Federal Regulations(207)	
MaineDOT, Bridge Maintenance(207)	
Maine Motor Transport Association (MMTA)(207)	
Maine Turnpike Regulations(800)	
Occupational Safety (U.S. Dept. of Labor)(207)	
Petroleum & Waste Oil Transport (DEP)(207)	
Posted Road Exemptions (Nearest MaineDOT Regional Off	
Region 1 (Southern Region)(207)	885-7000
Region 2 (Mid Coast Region)(207)	624-8200
Region 3 (Western Region)(207)	562-4428
그 그 사이 가장 되어 있다. 그렇게 그렇게 하는데 이렇게 하면 하면 하는데	
Region 4 (Eastern Region)(207)	941-4500
Region 5 (Northern Region)(207)	764-2060
Propane Delivery Tech. License (Prof & Fin Reg) (207)	624-8603
Safety Inspections/Regulations (State Police)(207)	624-8939
Sales Tax (Maine Revenue Services)(207)	624-9693
Seafood Transport (Marine Resources)(207)	624-6550
Solid Waste Transport (DEP)(207)	287-2651
State Fire Marshall(207)	626-3880
USDOT Numbers (FMCSA)(207)	622-8358

## MAILING ADDRESSES FOR COMMERCIAL VEHICLE INFORMATION, LAWS, and REGULATIONS

Maine Bureau of Motor Vehicles Motor Carrier Services 29 State House Station Augusta, ME 04333-0029

Fax: (207) 624-9086 (IRP/IFTA)

Fax: (207) 622-5332 (Overlimits/Operating Authority)

Fax: (207) 624-9390 (HVUT)

Physical Location: 101 Hospital Street, Route 9, Augusta

Hours of Operation:

Overlimit Permit Unit: 7:30 AM to 5:00 PM All Other Units: 8:00 AM to 5:00 PM

Note: Most BMV forms and rules are available online at www.maine.gov/sos/bmv/commercial.

Federal Motor Carrier Safety Administration (FMCSA) 40 Western Avenue Augusta, ME 04330 Fax: (207) 622-8477

Maine Bureau of the State Police, Troop K Commercial Vehicle Enforcement 20 State House Station Augusta, ME 04333-0020 Fax: (207) 287-5247

Maine Department of Environmental Protection Bureau of Hazardous Material & Solid Waste Control 17 State House Station Augusta, ME 04333-0017 Fax: (207) 287-7826

Maine Department of Marine Resources 21 State House Station Augusta, ME 04333-0021 Fax: (207) 624-6024

Maine Department of Professional & Financial Regulation Office of Licensing & Registration 35 State House Station Augusta, ME 04333-0035 Fax: (207) 624-8637 Maine Motor Transport Association (MMTA) 142 Whitten Road PO Box 857 Augusta, ME 04332-0857 Fax: (207) 623-4096

Maine Revenue Services 24 State House Station Augusta, ME 04333-0024 Fax: (207) 287-4028

Maine Turnpike Authority 2360 Congress Street Portland, ME 04102 Fax: (207) 871-7739

Occupational Safety & Health Administration U. S. Department of Labor 40 Western Avenue Augusta, ME 04330 Fax: (207) 622-8213

State Fire Marshal 52 State House Station Augusta, ME 04333-0164 Fax: (207) 287-6251

### 3. COMMERCIAL VEHICLE REGULATIONS

### A. Registration

Trucks, including eligible pickup trucks, must be registered as commercial vehicles for the actual gross weight of the truck and load, including the weight of any trailer or semitrailer and the load being drawn. A pickup truck registered as a passenger vehicle may not exceed 6,000 pounds gross vehicle weight unless it is towing: 1) a camper trailer; or, 2) a utility trailer weighing less than 2,000 pounds gross weight where the combined gross vehicle weight of the pickup and the utility trailer does not exceed 8,000 pounds. Otherwise, pickup trucks towing trailers where the combined gross vehicle weight exceeds 6,000 pounds must register as a commercial vehicle.

IRP Vehicles (see <a href="www.irponline.org">www.irponline.org</a>): Maine is a member of the International Registration Plan (IRP). Any Maine based power unit used or intended for use in two or more IRP jurisdictions to transport persons for hire or designed or

used for the transportation of property must be registered in the IRP if the unit:

- has two axles and a gross vehicle weight (GVW) or registered gross vehicle weight in excess of 26,000 pounds, or
- (2) has three or more axles, regardless of weight, or
- (3) is used in combination when the gross vehicle weight of the combination exceeds 26,000 pounds.

Recreational vehicles, vehicles displaying restricted plates, buses used in the transportation of chartered parties, or government owned vehicles are not required to be in the IRP (see the Department of the Secretary of State Rule Chapter 162 for more information at www.maine.gov/sos/cec/rules/29/250/250c162.doc).

Apportionable vehicles based in another IRP jurisdiction must have Maine on the cab card or have a valid Maine IRP trip permit. Non-apportioned vehicles operating intrastate must register in Maine or obtain trip permits.

Non-IRP Vehicles: except for certain motor vehicles registered in IRP, motor vehicles based in Maine must register in Maine based on the combined gross weight of the vehicle and maximum load to be carried. For truck tractor-semitrailer combinations, the power unit is registered for the combined gross weight and the semitrailer is registered for a nominal fee. A motor vehicle may not be operated in excess of the maximum weight allowed for its configuration, (see TABLE 1), without additional permits.

Taxes, Titles & Insurance: a registrant must pay an annual municipal excise tax before obtaining a Maine registration. Vehicles subject to the Title Law must be titled, or have a title application pending. Evidence of insurance is also required at the time of registration. Sales tax payment or proof of exemption from sales tax is required for a first time registration.

Boosters: once a commercial motor vehicle is registered in Maine, the gross weight may be increased for a period of one to eight months by paying an additional fee. Temporary increases in registered weight (boosters) convey all the privileges and responsibilities of registration. A temporary registered gross weight increase may not extend beyond the expiration of the regular registration. For

motor vehicles registered in the IRP, boosters are valid only in Maine.

### B. Heavy Vehicle Use Tax

Owners of vehicles registered or boosted to 55,000 pounds or more must file proof every year that the Federal Heavy Vehicle Use Tax (HVUT) has been paid. For vehicles base registered in Maine under the IRP, proof must be submitted at registration; other vehicles operating only within Maine must file proof within four months of vehicle registration. Otherwise, the vehicle's registration will be suspended. Proof of payment must be either a receipted copy of the Internal Revenue Service (IRS) Form 2290, Schedule 1, or a copy of both sides of the canceled check. Proof of HVUT payment must be provided to the Bureau of Motor Vehicles, Registration Unit, 29 State House Station, Augusta, Maine 04333-0029. Documents may be faxed to the Registration Unit at 624-9390. For assistance with HVUT payments, contact the Bureau of Motor Vehicles at 624-9000, extension 52151 or your nearest IRS office.

The IRS requires electronic filing of Form 2290 for each return reporting 25 or more vehicles. However, any taxpayer can file electronically. For more information on e-file, visit the IRS website at www.irs.gov/efile.

### C. Fuel Use Licensing And Reporting

Qualified Vehicles - vehicle operators using fuel other than gasoline must establish an account for fuel tax licensing and reporting if the motor vehicle:

- has a registered gross weight or actual weight of more than 26,000 pounds; or
- (2) has three or more axles on the power unit regardless of weight; or
- (3) is a bus with a seating capacity of 20 or more including the driver.

Each qualified motor vehicle must display either a Maine fuel use identification decal or an IFTA decal.

IFTA (see <a href="www.iftach.org">www.iftach.org</a>): Maine is a member of the International Fuel Tax Agreement (IFTA). Anyone operating qualified motor vehicles in two or more IFTA jurisdictions must license and report mileage and fuel consumption in all

IFTA jurisdictions through their base (home) jurisdiction. A Maine-based carrier operating out-of-state must license for IFTA with the Bureau of Motor Vehicles' Fuel Use Licensing Unit unless the carrier can satisfy the basing requirements in another jurisdiction. In IFTA, the carrier is issued one set of decals good for travel in all IFTA jurisdictions, and makes one quarterly fuel tax report to the base jurisdiction. Many IFTA jurisdictions require qualified gasoline-powered vehicles to license and report. Maine-based carriers with qualified gasoline-powered vehicles will license and report through the Bureau of Motor Vehicles' Fuel Use Licensing Unit.

Intrastate Carriers: Maine carriers operating qualified motor vehicles entirely within the State of Maine must license and display fuel decals. Carriers are exempt from filing fuel tax reports. However, carriers still must keep mileage records and report their fleet mileage and fuel consumed on their annual decal application.

Temporary License: Maine will issue a temporary (30-day) fuel license in lieu of a decal to operate a specific qualified vehicle. An application for a temporary license creates an annual account and requires the filing of fuel tax reports. Within 30 days the applicant will be issued an annual decal.

Trip Permits: In lieu of licensing and reporting, a carrier may obtain a 72-hour trip permit for a fee of fifty dollars.

### D. Overlimit Permits

General Information: an overlimit permit is required to transport non-divisible vehicles and/or loads which exceed the legal length, width, height, or weight limits established in Title 29-A, Chapter 21. Permits are not issued for divisible loads and such requests will be denied as these loads can be reduced to legal dimensions and/or weight. Permits are granted only for roads and bridges maintained by the Maine Department of Transportation and the NETC network. Municipalities may have their own restrictions and permitting systems in place and would have to be checked individually.

All vehicles transporting overlimit loads are subject to certain safety, routing, time of day, and holiday restrictions, as well as escort requirements. Additional information is available online at www.maine.gov/sos/bmv/commercial/olperms.htm.

Multi-State Permits: Maine, New Hampshire, Massachusetts, Vermont, and Rhode Island formed the New England Transportation Consortium (NETC). The NETC developed a common set of safety standards and procedures for issuing multi-state permits for the movement of non-divisible oversize/overweight combination vehicles and loads in interstate travel over predetermined routes within the five states. The issuing state issues a single permit on behalf of all affected states. To qualify for a multi-state permit, the vehicle and load may not exceed:

- 90 feet in length;
- (2) 13 feet 6 inches in height;
- (3) 14 feet in width (with an additional 6 inches of overhang allowed for the eaves on mobile and modular home components only);
- (4) 108,000 pounds for 5 axle and 120,000 pounds for 6 or more axle truck tractor-semitrailer combination vehicles.

Vehicles exceeding these limits must obtain separate permits in each applicable state.

Maine Turnpike Permit: the Maine Turnpike has its own specified size and weight limitations. Movement of oversized loads on the Maine Turnpike requires payment of a ten dollar (\$10) permit fee in addition to the applicable toll. Additional information is available by calling (800) 698-7747 or online at www.maineturnpike.com.

## E. 53 Foot Semitrailer Vehicles

Special permits for 53 foot semitrailers are no longer required. A combination vehicle not exceeding 74 feet in overall length that consists of a truck tractor and a single semitrailer whose length exceeds 48 feet but does not exceed 53 feet may be operated without a special permit on all highways in Maine provided that the semitrailer meets certain dimensional and safety requirements.

A combination vehicle exceeding 74 feet in overall length that consists of a truck tractor and a single semitrailer whose length exceeds 48 feet but does not exceed 53 feet may operate only on the following roads and within 1 mile of these roads:

- the Maine Interstate Highway System (including the Maine Turnpike),
- (2) the Scarborough Connector from I-295 in South Portland to US Route 1 in South Portland,
- (3) the South Portland Spur from I-95 in South Portland to US Route 1 in South Portland, and
- (4) US Route 1 from I-95 in Brunswick to the Congress Street interchange in Bath.

Additionally, 53 foot trailers are subject to the following dimensional requirements and safety conditions:

- the wheelbase of the semitrailer, measured as the distance from the kingpin to the center of the rearmost axle of the semitrailer, may not exceed 43 feet,
- (2) the kingpin setback of the semitrailer may not exceed 3 ½ feet.
- (3) the rear overhang of the semitrailer may not exceed 35 percent of the wheelbase,
- (4) the semitrailer must be equipped with a rear underride guard, vehicle lights, and reflective material as prescribed by statute, and
- (5) the semitrailer must be equipped with a conspicuous wide-turn sign.

For additional information please reference Title 29-A M.R.S.A. §2390.

F. Interstate and Intrastate Operating Authority/Unified Carrier Registration (UCR)/Insurance Requirements

Interstate Carriers providing transportation of cargo or passengers for compensation must obtain Operating Authority (MC Number) from the Federal Motor Carrier Safety Administration (FMCSA). Carriers may apply online at: www.fmcsa.dot.gov/registration-licensing/online-registration/onlineregdescription.htm

Maine is a member of the Unified Carrier Registration Agreement (UCRA). The UCR Agreement requires all interstate for-hire motor carriers transporting property or passengers and interstate motor private carriers transporting property, as well as brokers, freight forwarders, and leasing companies (collectively referred to as UCR registrants) to register with the United States Department of Transportation (USDOT) and to pay UCR fees.

Maine-based carriers must register in Maine to satisfy this requirement. Annual fees are based on fleet size. The revenue generated must be used for commercial vehicle safety programs and incentives. For purposes of determining the number of fleet vehicles, a "commercial motor vehicle" is defined as a self-propelled vehicle used on the highways in commerce primarily to transport passengers or cargo, if the vehicle has a gross vehicle weight rating or gross vehicle weight of at least 10,001 pounds, whichever is greater, is designed to transport more than 10 passengers, including the driver, or is used in transporting hazardous materials in quantities requiring placarding. Online UCR registration is available at www.maine.gov/online/ucr.

Intrastate Carriers of passengers for compensation (for hire) must contact the Bureau of Motor Vehicles' Operating Authority Unit to ensure compliance with Maine's insurance and operating authority requirements. Owners of taxis, limousines, buses, and consumer rental vehicles must maintain continuous proof of insurance based on the manufacturer's designed maximum seating capacity.

Further information on these requirements is available from the Operating Authority Unit or online at www.maine.gov/sos/bmv/commercial/oassrs.htm.

### G. Commercial Vehicle Safety Inspections

Most commercial vehicles, (including trucks, buses, trailers, semitrailers and converter dollies), which use public highways in interstate or intrastate commerce to transport passengers or property are required to have an annual commercial vehicle safety inspection when:

- the gross vehicle weight or gross vehicle weight rating of the vehicle or combination vehicle exceeds 10,000 pounds; or
- (2) the vehicle is designed to transport more than 15 passengers including the driver; or
- (3) the vehicle is used in the transportation of hazardous materials which require placarding.

Commercial vehicles displaying a current certificate of inspection from any state or federally approved commercial vehicle inspection program are exempt from inspection until the normal expiration of the certificate. Storage trailers operating under the provisions of Title 29-A M.R.S.A. §462(8) are also exempt from annual inspections. For information on vehicles exempted from annual inspections, contact Maine State Police Troop K, Commercial Vehicle Enforcement at (207) 624-8939.

### H. Hazardous & Nonhazardous Waste & Materials Carriers

Carriers of petroleum, waste oil, and solid waste must contact the Department of Environmental Protection at (207) 287-2651 or online at <a href="https://www.maine.gov/dep">www.maine.gov/dep</a> for information about the required transport licenses. Propane haulers should contact the Maine Department of Professional & Financial Regulation. Those transporting explosives should contact both the State Fire Marshal and the Federal Highway Administration. Federal Hazardous Materials Regulations may also apply to motor vehicles of any size which transport certain hazardous materials, wastes, or substances, including bulk cryogenic liquids. Contact the Federal Motor Carrier Safety Administration at (207) 622-8358 for further information. The Maine State Police may be contacted at (207) 624-8939 for information about placarding and hazardous materials regulations.

# I. Federal Motor Carrier Safety & Insurance Regulations

Federal Motor Carrier Safety Regulations (FMCSR) apply to the operation of commercial motor vehicles which transport property or passengers in interstate commerce. The regulations also apply to commercial vehicles operating entirely within Maine. The FMCSR definition of a "commercial motor vehicle" is as described in the preceding paragraph on Commercial Vehicle Safety Inspections. There are certain exemptions for carriers operating within a 100 air mile radius of their home base. See "Motor Carrier Safety Rules" chart for safety regulations applicable to property carriers.

Federal Minimum Financial Responsibility (Insurance)
Requirements apply to interstate "for hire" motor carrier
operations and to the interstate transportation of any
quantity of a hazardous material. These requirements also
apply to the transportation of hazardous materials in a
portable or cargo tank with a capacity exceeding 3,500

gallons, whether transported entirely within Maine or interstate. See "Motor Carriers of Property Insurance Reference Chart" for insurance requirements or contact the Federal Motor Carrier Safety Administration at (207) 622-8358 for further information.

### J. Federal Drug Testing Requirements

Federal regulations require that all motor carriers operating commercial motor vehicles be subject to testing for marijuana, cocaine, opiates, amphetamines, and phencyclidine (PCP). "Commercial motor vehicles" for the purposes of drug testing include:

- a single vehicle with a gross vehicle weight rating or registered weight exceeding 26,000 pounds;
- (2) a combination of vehicles with a combined gross vehicle weight rating or registered weight exceeding 26,000 pounds if the vehicle being towed exceeds 10,000 pounds gross weight;
- (3) passenger vehicles designed to transport 16 or more passengers (including the driver); and
- (4) vehicles transporting hazardous materials which require placarding.

If a driver is subject to the Federal Motor Carrier Safety Regulations pertaining to Commercial Driver's Licenses (CDL's) and the vehicle meets the definition of a commercial vehicle described in paragraph G, then the driver must be tested.

For information concerning drug testing procedures and programs, see the chart on "Motor Carrier Safety Rules" or contact the Federal Motor Carrier Safety Administration at (207) 622-8358.

### K. USDOT Identification Numbers

All motor carriers seeking to operate commercial motor vehicles across state borders into other jurisdictions must, unless exempted, obtain a U. S. Department of Transportation (USDOT) number. The USDOT number must be displayed on both sides of the commercial motor vehicle prior to beginning operation. Intrastate motor carriers must also have a USDOT number if the truck has a gross weight greater than 26,000 pounds or has three or more

axles on the power unit. Display of the USDOT number is not required on intrastate trucks except for intrastate hazardous materials carriers. USDOT number applications are available from any Bureau of Motor Vehicles branch office or by calling 624-9000, extension 52133.

### L. Headlight Illumination

Maine Public Law 1997, Chapter 249 requires that the headlights of all motor vehicles operating on a public way must be illuminated whenever the vehicle's windshield wipers are in constant use. This requirement is in addition to requiring headlight illumination if operating at night or whenever, due to weather conditions, vehicles or persons cannot be seen for a distance of 1,000 feet ahead.

### 4. GROSS WEIGHT LIMITS

## A. Maine General Law

Maine's General Law gross weight limit applies to the following highways:

- (1) Interstate 95 from the New Hampshire State Line to Exit 113 (Augusta Cushnoc Bridge) which includes the Maine Turnpike; and
- (2) all non-Interstate highways.

Maine's General Law provides that the total weight of a vehicle or a combination of vehicles, plus their load, is limited by the number of axles to the gross vehicle weights listed in TABLE 1.

TABLE 1 - GENERAL LAW GROSS WEIGHT LIMITS

Total Axles	Gross Vehicle Weight			
2 Axles	34,000 pounds			
3 Axles	54,000 pounds			
4 Axles	69,000 pounds*			
5 Axles	s 80,000 pounds			
6 Axles	100,000 pounds**			

<sup>·</sup> Also applies to all single unit vehicles over four axles.

<sup>\*\*</sup> Applies only to a combination vehicle consisting of a three axle truck tractor towing a tri-axle semitrailer unit that is operating on (1) the General Law highways listed above or (2) any interstate highway in Maine for as long as a federal law exempting Maine from the 80,000 pound interstate limit is in effect. The 80,000 pound limit applies to all other combination vehicles over 4 axles, except for certain vehicles carrying special commodities which are allowed additional weight tolerances. See Section 9.C.

TABLE 2 shows the gross weight limit reduction for four or more axle combination vehicles having short wheel bases. The "Distance In Feet" noted is that between the centers of the extreme axles of the vehicle, excluding the steering axle, measured to the nearest foot.

TABLE 2 - COMBINATION TRUCK GROSS VEHICLE WEIGHT LIMITS FOR SHORTER WHEEL BASE VEHICLES

ON TRUCKS	ER COMBINATIO	ALL OTH	SPECIAL 6 AXLE COMBINATION		
	GROSS VEHICLE WEIGHT	DISTANCE		GROSS VEHICLE WEIGHT	DISTANCE
5+ AXLES	4 AXLE	IN FEET	OTHER	SC	IN FEET
Reduced	59,000	8	82,000	90,000	27
2,000	60,000	9	84,000	92,000	28
Pounds	61,000	10	86,000	94,000	29
From	62,000	11	88,000	96,000	30
80,000	63,000	12	90,000	98,000	31
For	64,000	13	92,000	100,000	32
Each	65,000	14	94,000		33
Foot	66,000	15	96,000		34
Less	67,000	16	98,000		35
Than	68,000	17	100,000		36
24 Feet	69,000	18	1000		
70,000		19			
72,000	Over 18	20			
74,000	Feet	21			
76,000	Limited	22			
78,000	To	23			
80,000	69,000	24			
80,000		25			

### Notes on TABLE 2

- (1) "Special 6 Axle Combination" may be only a three axle truck tractor (not truck) hauling a semitrailer with a rear tri-axle.
- (2) Four and five axle combinations hauling certain special commodities are also eligible for a 10 percent GVW tolerance up to 75,900 pounds for a four axle combination and 88,000 pounds for a five axle combination if traveling on the Maine Turnpike or off the Interstate Highway System. (See Section 9.C.)
- (3) "SC" means a Special 6 Axle Combination truck registered for at least 90,000 pounds that is hauling certain special commodities. (See Section 9.C.)
- (4) "OTHER" means all other Special 6 Axle Combination trucks.

## B. Interstate Highway System.

For operation on the Interstate Highway System, excluding those segments of the Interstate Highway System listed in Section 4.A., the weight of the vehicle or combinations of vehicles, plus their load, is limited by Bridge Formula B, modified. In addition, the Bridge Formula also limits the total weight of any group of consecutive axles of a vehicle or combination of vehicles according to the distance between the centers of the extreme axles in the group. The greatest load allowed is 80,000 pounds. TABLE 3 lists the maximum Bridge Formula B weight limits for groups of axles containing from two to seven axles arranged by the distance between extreme axles in the group.

Bridge Formula B, modified is: W = 500(LN/(N-1) + 12N + 36)where:

- W = overall gross weight on any group of two or more consecutive axles;
- L = overall distance in feet between the centers of extreme axles for any group of two or more consecutive axles; and
- N = number of axles in the group under consideration.

The following are exceptions to the use of the Bridge Formula on the Interstate System:

- single axles are limited to 20,000 pounds for vehicles over 73,280 pounds GVW, and 22,000 pounds for vehicles 73,280 pounds GVW or less;
- (2) tandem axles are limited to 34,000 pounds;
- (3) two consecutive tandem axles may carry 34,000 pounds each if there are at least 36 feet between centers of extreme axles;
- (4) all three axle trucks with brakes on the wheels of all axles may be operated with a gross weight of 48,000 pounds if the distance between extreme axles is at least:
  - a. 16 feet when hauling construction materials, or
  - b. 18 feet when hauling forest products, or hauling raw ore from mine or quarry to place of processing.

TABLE 3 - INTERSTATE AXLE GROUP "BRIDGE FORMULA" WEIGHT LIMITS

Centers of Extreme Axles In Axle Group	2 Axles	3 Axles	4 Axles	5 Axles	6 Axles	7 Axles
4	34,000	2 WYIGE	4 WYIES	2 WYTES	o wyres	/ WYTES
5	34,000					
6	34,000					
7	34,000		5 V	LE GROUPS	TM	
8	34,000	34,000	An.	de GROOPS	114	
More than 8	38,000	42,000		7771	ESE SPACI	Mag
9	39,000	43,000		111	ESE SPACE	MGS
10	40,000	43,500			IMPRAC	TTCAT
11	41,000*	44,500			THERAC	TTCM
12	42,000*	45,000	50,000			
13	43,000*	46,000	50,500			
14	44,000*	46,500	51,500			
15		47,500	52,000			
16		48,000	52,500	E0 000		
		49,000	53,500	58,000		
17 18		200 C 000 \$455 455 57	54,000	58,500		
19		49,500		59,500		
		50,500	54,500	60,000	ee 000	
20		51,000	55,500	60,500	66,000	
21		52,000	56,000	61,000	66,500	
22		52,500	56,500	62,000	67,000	
23		53,500	57,500	62,500	68,000	
24		54,000	58,000	63,000	68,500	74,000
25		55,000	58,500	63,500	69,000	74,500
26		55,500	59,500	64,500	69,500	75,000
27		56,500	60,000	65,000	70,000	76,00
28		57,000	60,500	65,500	71,000	76,50
29		58,000	61,500	66,000	71,500	77,00
30		58,500	62,000	67,000	72,000	77,50
31		59,000	62,500	67,500	72,500	78,000
32		60,000	63,500	68,000	73,000	78,500
33		y	64,000	68,500	74,000	79,500
34			64,500	69,500	74,500	80,000
35			65,500	70,000	75,000	
36			66,000**		75,500	
37			66,500*1		76,000	
38			67,500**		77,000	
39			68,000	72,500	77,500	
40			68,500	73,000	78,000	
41			69,500	73,500	78,500	
42			70,000	74,500	79,000	
43			71,000	75,000	80,000	
44			71,500	75,500		
45			72,000	76,000		
46				77,000		
47			Greater	77,500		
48			Loads	78,000		
49			Not	78,500		
50			Practical	79,500		
51	*****			80,000		

- \* 40,000 lbs. if GVW is 73,280 lbs. or more.
- \*\* If two tandems, 68,000 lbs.

### C. Six-Axle Truck Weight Pilot Project

Federal legislation enacted December 19, 2009 authorized a pilot project to allow only a six axle vehicle combination consisting of a three axle truck tractor with a tri-axle semitrailer having a maximum gross weight of 100,000 pounds to operate on all portions of the interstate highway system in Maine if otherwise in compliance with all other requirements of Title 29-A M.R.S.A. Vehicle combinations operating under the exemption from the federal vehicle interstate weight limitations are subject to the Maine General Law Gross Weight Limits (see 4.A.) for as long as a federal law exempting Maine from the 80,000 pound interstate limit is in effect.

### 5. AXLE WEIGHT LIMITS

- A. Groups of closely spaced axles shall be treated as follows:
  - axles whose centers are less than 4 feet apart shall be considered a single axle unit; and
  - (2) a single axle whose center is closer than 10 feet, or if it is a steering axle 9 feet, to a tri-axle unit shall be considered part of that tri-axle and not add to the allowable load capacity of that tri-axle unit.
- B. The axle weights, fine tolerances, and distance limits for axle units are illustrated in TABLE 4 below.

# TABLE 4 - AXLE UNIT WEIGHT LIMITS & TOLERANCES (Tolerances are in italics)









	SINGLE A)	(LE
INTERSTATE	22,000	Up to 73,280 lb. GVW.
	20,000	Over 73,280 lb. GVW.
Federal Exemption*	22,400	6 axle combinations only
NON-INTERSTATE**		DESCRIPTION OF THE PARTY OF THE
General Freight	22,400	
Special Commodity***	24,200	
	TANDEM	
INTERSTATE	34,000	
Federal Exemption*	41,000	6 axle combinations only
NON-INTERSTATE**		
General Freight	38,000	
	41,000	6 axle combinations only
Special Commodity***	44,000	5 or more axle trucks.
Things with a solution of the solution	46,000	All other trucks.
	TRI-AXLE	THE RESERVE OF THE PERSON NAMED IN
INTERSTATE	TABLE 3	
Federal Exemption*	50,000	6 axle combinations only
NON-INTERSTATE**		THE RESERVE OF THE PERSON NAMED IN
General Freight	48,000	
ALCOHOL: S	50,000	6 axle combinations only
Special Commodity***	54,000	
Forest & Potatoes****	64,000	4 axle single unit only.

- Only applies to a 6-axle vehicle combination consisting of a 3-axle truck tractor and a tri-axle semitrailer for as long as a federal law exempting Maine from the 80,000 pound interstate limit is in effect.
- \*\* Also applies to those sections of Interstate 95 listed at the beginning of Section 4.
- \*\*\* "Special Commodities" are listed in Section 9.C.(4).
- \*\*\*\* "Forest Products" include bark, sawdust, firewood, pulpwood, wood chips, or logs. Potato haulers must register the 4-axle truck as a farm truck.

WARNING: Fines for exceeding tolerance weights are calculated based upon the "General Freight" weight limit.

### C. Loads shall be distributed as follows:

(1) no single axle of a tandem unit may support more than 60 percent of the total weight supported by the tandem unit (no violation accrues if neither axle of the tandem exceeds the weight legally allowed on a single axle unit for the same vehicle);

- (2) no single axle of a tri-axle unit may support more than 40 percent of the total weight supported by the triaxle unit; and
- (3) the allowable gross weight of a vehicle may not be increased by adding a "trailing axle" unless this axle supports at least 50 percent of the added weight permitted by adding that trailing axle.

## D. Weight Limited By Tire Size

Regardless of any other applicable weight limits, all loads shall be limited to 600 pounds per inch of tire width, manufacturer's rating, except for farm trucks transporting potatoes directly from the field to the place of storage or to a processing facility during the potato harvesting season.

For additional information regarding the above axle and gross weight limits, please contact the Maine Department of Transportation, Bridge Maintenance at (207) 624-3580.

#### RESPONSIBILITY FOR OPERATION OF A MOTOR VEHICLE

It is prima facie evidence that the person, firm, or corporation holding the operating authority, (or the vehicle registration, in the absence of operating authority), is responsible for the operation of the vehicle.

### BRAKES

Every truck, truck tractor, trailer and semitrailer must be equipped with adequate brakes acting on all wheels of all axles, except vehicles meeting any of the following conditions:

- A. any truck or truck tractor having three or more axles manufactured before August 1, 1980 need not have brakes on the steering axle wheels (vehicles with two steering axles must have brakes on one steering axle);
- B. any trailer or semitrailer that has a gross weight of 3,000 pounds or less;
- C. any vehicle towed by a wrecker;
- D. any vehicle that meets the braking requirements of the motor carrier safety regulations promulgated or accepted by

### the U. S. Department of Transportation;

- E. any semitrailer designed and used exclusively for the dispensing of cable from reels or to support the ends of poles while being transported, as long as the gross weight of the semitrailer and supported load does not exceed 12,000 pounds; or
- F. any dolly axle on a farm truck that is transporting agricultural products or supplies if such an axle does not increase the allowable gross weight of the vehicle.

### 8. PROJECTING OBJECTS & TRAILERS

Vehicles carrying objects that project more than 4 feet from the rear of the vehicle must, during the period of one-half hour after sunset to one-half hour before sunrise, carry a red light at or near the rear end of the projecting object(s). At all other times, the vehicle must carry a clean red cloth of the dimensions 12 inches by 12 inches attached at or near the end of the projecting object(s).

During the hours when lights are required, a vehicle carrying logs that project more than 4 feet from the rear of the vehicle is required to display a red reflector or to paint reflectorized paint on the end of the log projecting furthest to the rear. The reflector or reflectorized paint must be properly maintained, and must be located and be of a size which is sufficient to reflect at night on an unlighted highway the undimmed headlights of a vehicle approaching the rear of the vehicle from a distance of at least 200 feet.

A load must be covered or otherwise secured or confined to prevent any portion of the load from falling from or spilling out of the vehicle.

Trailers, semitrailers, or vehicles being towed must, in addition to the tow bar or coupling device, have a safety chain or steel cable made of not less than one-quarter inch wire so attached as to prevent breakaway from the towing vehicle. (This requirement does not apply to truck tractor and semitrailer units equipped with a fifth wheel mechanism.)

Trailers that are wider than the towing vehicle must be equipped with reflective material or a lamp on each front corner that is visible to oncoming traffic.

### 9. OPERATIONAL VEHICLE WEIGHTS

The operational vehicle weights described in this section are applicable on the following highways:

- (1) Interstate 95 from the New Hampshire State Line to Exit 113 (Augusta Cushnoc Bridge) which includes the Maine Turnpike; and
- (2) all non-Interstate highways.

### A. General Tolerance

Provided that gross, axle and tire limits are not exceeded, vehicles may operate at a gross weight exceeding the current registration by the greater of 2 1/2 percent or 500 pounds.

### B. Maximum Operational Gross Vehicle Weight (GVW)

Note: See Section C. for exceptions to the following rules.

A three axle truck tractor (not truck) and tri-axle semitrailer combination vehicle may operate at a maximum of 100,000 pounds GVW if:

- the vehicle is registered or apportioned for 100,000 pounds;
- (2) the distance\* between extreme axles, excluding the steering axle, is at least 36 feet to the nearest foot;
  - \* The 100,000 pound maximum GVW shall be reduced 2,000 pounds for each foot this distance is less than 36 feet, to the nearest foot.
- (3) the minimum distance between the steering axle and the first axle of the tandem is at least 10 feet to the nearest foot; and
- (4) the maximum weight shall not exceed 41,000 pounds on the tandem axle and 50,000 pounds on the tri-axle.

For all vehicles manufactured, modified, or retrofitted with liftable or variable load suspension axles after October 30, 1991, such axles are permitted only under the following conditions:

- only one liftable or variable load axle may be present on the truck tractor unit, and such axle must be legally part of the tandem axle group;
- (2) only one liftable or variable load axle may be present on the semitrailer unit, and such axle must be legally part of the tri-axle group; and
- (3) the axle weight rating of the lift axle must conform to the expected loading of the suspension and be at least 20,000 pounds or more.

# C. "Special Commodity" Weight Tolerances.

- (1) While actively engaged in the exclusive transport of the commodities listed in subsection (4), vehicles will be allowed special weight tolerances.
- (2) The special weight tolerances are:
  - a. 10 percent over the maximum gross weights (up to 80,000 pounds) listed in TABLE 1;
  - b. 85,000 pounds GVW for certain six axle single unit trucks carrying only forest products. See Item (5);
  - c. 94,000 pounds GVW for certain four axle single unit truck trailer combination vehicles. See Item (6);
  - d. 100,000 pounds GVW for combination vehicles consisting of a three axle truck tractor (not truck) with a tri-axle semitrailer that is registered or apportioned for at least 90,000 pounds GVW;
  - e. Axle weight limits: See TABLE 4, "Special Commodity".

### (3) Restrictions include:

- a. wheel base reductions for 4 or more axle combinations;
- 600 pounds per inch width of tire, manufacturer's rating;
- c. unless otherwise indicated in this section, the vehicle must be registered or apportioned for the maximum legal weight allowed for that vehicle configuration under Maine law; and

- d. for operation at 100,000 pounds gross weight, the distance between the extreme axles of the vehicle, excluding the steering axle, must be at least 32 feet to the nearest foot (See Table 2 for GVW reductions if this distance is less than 32 feet).
- (4) The vehicle must be loaded entirely with the following commodities:
  - a. materials or unset concrete intended for highway construction and carried in dump or transit mix trucks;
  - b. manufacturer's concrete products;
  - c. raw ore from a mine or quarry to the place of processing;
  - d. unprocessed milk;
  - e. refrigerated products when they constitute the majority of products carried in a sealed vehicle;
  - f. building materials that absorb moisture during delivery originating and terminating within the State;
  - g. incinerator ash;
  - h. unconsolidated rock materials including limestone, bark, pulpwood, firewood, logs, sawed lumber, bolts, soil, dimension lumber, road salt, solid waste, farm produce, sawdust, and wood chips.
- (5) A four axle single unit truck, two axle trailer combination vehicle carrying the commodities listed in (4) above may operate at a maximum gross vehicle weight of 94,000 pounds under either of the following conditions:
  - a. the trailer unit is registered for at least 28,000 pounds gross weight and the combined registered weight for the truck and trailer is at least 94,000 pounds gross weight; or
  - b. the truck is registered for at least 94,000 pounds.

Other restrictions apply. Contact the BMV, Motor Carrier Services Office for further information.

## D. Posted Road Exemptions

Each spring, in order to prevent increased pavement damage from heavy truck axles during freeze and thaw cycles, MaineDOT evaluates its State and State-Aid highways to determine whether weight restrictions should be imposed. For a period of time, certain roads may be "posted" with weight limit restrictions that are significantly lower than the regular weight limit.

When a road is posted, the weight limit of vehicle and load is 23,000 pounds. Unexempted vehicles will be subject to a weight violation if they exceed this weight when traveling on a posted road that is not considered to be solidly frozen. The determination of whether a road is frozen is made by an enforcement officer at a roadside stop, not by MaineDOT. A general guideline that the officer may use at his or her discretion is that a road is considered to be "frozen" if the air temperature is below 32 degrees Fahrenheit and there is no standing water on the road.

The following vehicles are exempt from posted highways regulations:

- any vehicle or combination of vehicles registered for a gross vehicle weight of 23,000 pounds or less;
- (2) any unloaded vehicle (excluding special mobile equipment) carrying only tools and equipment necessary for the vehicle's proper operation regardless of registered weight;
- (3) MaineDOT highway maintenance vehicles or vehicles under the direction of a public jurisdiction engaged in emergency highway maintenance with the permission of the Maine Department of Transportation;
- (4) passenger cars, pickup trucks, emergency vehicles, school buses, and vehicles with fewer than 4 axles under the direction of a public utility and engaged in plant maintenance or repair;
- (5) vehicles carrying any home heating fuel to a private consumer, gasoline, groceries, bulk milk, bulk feed, solid waste, rubbish, or medical gases provided that an exemption certificate is obtained from MaineDOT.

The vehicle must be registered in excess of 23,000 pounds and carry a partial load with a gross weight not to exceed the weight indicated on the exemption certificate. Applicants for certificates must present certified weigh slips for the empty weight of the vehicle;

(6) any combination vehicle of five or more axles with a GVW of 80,000 pounds or less hauling perishable products, and having in the vehicle a permit issued by MaineDOT.

For lists of currently posted roads and information on obtaining exemption permits, check the MaineDOT website at: www.maine.gov/mdot/postedroads/index.htm or contact the nearest MaineDOT Regional Office (see Section 1 -Contacts).

<u>Please Note</u>: Many municipalities impose similar spring weight restrictions on their local road systems. For information about local road postings, please contact the appropriate municipal office.

### 10. OCEANGOING CONTAINERS

Through joint action of the Maine Department of Transportation and the Secretary of State, carriers transporting sealed oceangoing containers on roads or bridges maintained by the Maine Department of Transportation may, under certain predefined conditions, be issued Oceangoing Container (OGC) Permits authorizing operation at weights in excess of the legal weight allowed for the transporting vehicle configuration. OGC Permits are vehicle and route specific; issued for a predetermined number of trips; and expire one year from the date of issue. An annual administrative fee is charged along with a highway system impact fee based on the road mile distance within the State of Maine between the container's port of entry/exit or railhead removal point and its destination or origin point. For additional information, contact the Overlimit Permit Unit at (207) 624-9000 extension 52134 or see the Department of the Secretary of State Rule Chapter 164 at www.maine.gov/sos/cec/rules/29/250/250c164.doc.

# MOTOR CARIERS OF PROPERTY INSURANCE REFERENCE CHART

NOTE: The type of carriage listed applies to vehicles with a gross vehicle weight rating of 10,000 pounds or more unless otherwise specified.

Operation Type	Commodity	Minimum Insurance Coverage Required		
For hire, not federally regulated, all weights (Maine law)	General, not included in references below:	\$350,000		
For-hire interstate, or foreign Commerce	Non-hazardous - general	\$750,000		
For-hire and private commerce; Interstate, Foreign, or Intrastate	Hazardous substances as defined in 49 CFR 171.8 transported in cargo tanks, portable tanks, or hopper-type vehicles with capacities in excess of 3,500 water gallons; or in bulk Division 1.1, 1.2, and 1.3 materials, Division 2.3, Hazard Zone A, or Division 6.1, Packing Group 1, Hazard Zone A material; in bulk Division 2.1 or 2.2; or highway route controlled quantities of a Class 7 material, as defined in 49 CFR 173.403.	\$5,000,000		
For-hire and private in commerce Interstate Foreign – any quantity Intrastate – bulk only	Oil listed in 49 CFR 172.101, hazardous waste, hazardous materials and hazardous substances defined in 49 CFR 171.8 and listed in 49 CFR 172.101, but not mentioned above or below.	\$1,000,000		
For hire and private in commerce Interstate, Foreign, or Vehicles of GVWR less than 10,000 lbs.	Any quantity of Division 1.1, 1.2, or 1.3 material; any quantity of a Division 2.3, Hazard Zone A, or Division 6.1, Packing Group 1, Hazard Zone A material; or highway route controlled quantities of a class 7 material as defined in 49 CFR 173.403	\$5,000,000		
For hire in commerce Interstate or Foreign	Property (nonhazardous)-vehicles of GVWR less than 10,000 lbs.	\$300,000		
Short term light truck rentals	Subject to for hire and hazmat insurance if applicable	\$125,000 CSL OR \$50,000/\$100,000/\$25,000		
Short term truck rentals over 26,000 registered GVWR	Subject to for-hire and hazmat insurance if applicable	\$350,000		


### MOTOR CARRIER SAFETY RULES PROPERTY CARRIERS – BY DISTANCE AND GROSS WEIGHT


	PLAC- ALL; ANY WEIGHT- ANY RADIUS	INTRA <100 MI. 10,001 – 26K	INTRA <100 MI. >26K	INTRA >100 MI. 10,001 – 26K	INTRA >100 MI. >26K	INTER <100 MI. 10,001 – 26K	INTER <100 MI. >26K	INTER >100 MI. 10,001 – 26K	INTR >100 MI >26K
CDL and Endorsements As Needed	Х		х		X		Х		х
Application for Employment	х			×	X	×	×	X	X
Pre-Hire Inquiries & Investigations	×	X Limited	X Limited	x	x	×	x	×	X
Annual Review Of Driving Record	×	×	X	×	×	×	x	×	×
Record of Violations	х	x	×	×	×	×	×	x	Х
Medical Examiner Certificate	х			X1	X1	×	х	x	x
Substance Abuse Testing	×	X2	X	X2	X	X2	X	X if CDL	Х
Driving Rules (Part 392)	X	x	x	X	×	×	×	×	X
Parts and Accessories (Part 393)	X	x	×	×	X	×	×	×	X
Hours of Service Requirements	х			×	x	×	×	х	x
Log Books	3			Х	Х	4	4	Х	Х
Vehicle Maintenance Records	×	X	×	x	×	×	×	x	×
Out of Service Criteria	х	х	×	×	×	x	x	х	X
Driver Vehicle Inspection Reports	×	X5	X5	X	×	x	x	×	×
Driver Pre-trip & Post-trip Inspection	x	x	×	×	x	×	x	x	x
Periodic Vehicle Inspection (Federal)	6	6	6	6	6	6	6	6	6
Brake Inspector Qualifications	x	X	X	×	X	X	X	X	X
Haz Mat Driving & Parking Rules	×								
US DOT Number	7		×		×	X	X	х	x

<sup>(1)</sup> Exempt from hearing portion of physical exam. (2) Only applicable to carriers/CDL drivers operating passenger vehicles designed to carry 16 or more passengers (P endorsement). (3) No log books under 100 MILES EXCEPT IF REQUIRED BY NOTE 4. (4) Some conditions apply to log book exemptions. (5) Applicable if carrier operates more than one commercial motor vehicle. (6) State mandated periodic motor vehicle inspection also applies. (7) All interstate and intrastate greater than 26K. Anyone who knowingly or intentionally violates or causes the violation of a safety rule that results in death or serious injury commits a Class C crime.


## GROSS VEHICLE WEIGHTS

(SPECIAL COMMODITY ALLOWANCES IN PARENTHESES)













Max. 69,000 lbs. (75,900)




Max. 69,000 lbs. (75,900)


TANDEM AXLE TRUCK or TRACTOR SEMI-TRAILER




Max. 80,000 lbs. (88,000)




Max. 80,000 lbs. (88,000)







Max. 80,000 lbs. (88,000) (94,000 lbs. -See SEC.9D(5))




Max. 80,000 lbs. (88,000)



(SEE SECTION #9)

Gross weight limits on the Interstate for all vehicles and commodities are controlled by Bridge Formula (Table 3.) However, in no case shall the maximum G.V.W. on the Interstate exceed the limits established in Table 1.

# GROSS VEHICLE DIMENSIONS



- \* If >45 to 48 feet, then the distance between the center of the rear axle of the tractor and the center of the rear axle of the trailer must not exceed 38 feet.
- # Not over 74 feet if including a semitrailer > 48 feet long.
- ★ Tree length logs may extend 8 1/2 ft. beyond the vehicle provided the extension is not more than 25% of the log length. (NON-INTERSTATE)

# INTERSTATE EXTENDED VEHICLE LENGTHS

Applies also to certain designated Federal Aid Primary highways and permitted access to that system of highways.

